


MELF 金屬皮膜無腳電阻器


MELF METAL FILM RESISTOR

DIMENSION

MFM TYPE



MFH TYPE



Coating color: Blue.
塗裝色: 藍色

SPECIFICATIONS

Type	Size	Dimension s(mm)			
		L	D	S	
MFM	0102	2±0.1	1.3±0.1	0.55±0.1	0.1±0.05
	0204	3.5±0.2	1.45±0.1	0.6±0.1	1.40 1.20
	0207	5.7±0.2	2.2±0.1	0.8±0.2	2.30 2.00
MFH	0309	9.5±0.3	3.6±0.3	2.2±0.2	0.4±0.1
	0411	11.2±0.3	4.7±0.3	2.6±0.2	0.5±0.1
	0515	15.2±0.3	5.3±0.3	2.6±0.2	0.5±0.1

Type	Size	POWER RATING	MAX WORKING VOLTAGE	MAX OVERLOAD VOLTAGE	T.C.R.	RESISTANCE RANGE			
						±0.1%	±0.25%	±0.5%	±1%
MFM	0102	1/8Ws	150V	300V	±15ppm ±25ppm ±50ppm ±100ppm	50 ₀ -56K	50 ₀ -100K	1 ₀ -1M	0 ₀ 22-2M
						100 ₀ -56K	100 ₀ -100K	1 ₀ -1M	0 ₀ 22-2M
	0204	1/4Ws	200V	400V		100 ₀ -56K	100 ₀ -100K	1 ₀ -1M	0 ₀ 5-2M
						100 ₀ -100K	10 ₀ -560K	1 ₀ -5M	0 ₀ 22-5M
	0207	1/2Ws	300V	600V		100 ₀ -100K	10 ₀ -560K	1 ₀ -5M	0 ₀ 22-5M
						100 ₀ -100K	10 ₀ -560K	1 ₀ -5M	0 ₀ 5-5M
MFH	0309	1Ws	500V	1000V	-----	10 ₀ -100K	1 ₀ -1M	0.1 ₀ -1M	
	0411	2Ws			-----	10 ₀ -100K	1 ₀ -1M	0.1 ₀ -1M	
	0515	3Ws			-----	10 ₀ -100K	1 ₀ -1M	0.1 ₀ -1M	

額定電壓是以 $\sqrt{\text{功率}(W) \times \text{阻值}(\Omega)}$ 計算所得的值及以規格表中所列最高使用電壓兩者相較小者。

Rated-Voltage= $\sqrt{P(W) \times R(\Omega)}$ or Max.working voltage, whichever lower.